

24 APR 2001

09/830239

A HOUSING, WITH A TUBULAR CONNECTOR, FOR A HEART STIMULATOR

Technical field of the invention.

5 The present invention relates to pacer housings and more particularly to those parts of the housing intended for connection to the electrode leads.

Background of the invention.

10 Implantable pacers normally comprise a pacer housing (also called can) containing electronic circuitry and a unit for electric power as well as different electrodes which are connected to the interior parts in the pacer housing and which are to be implanted in or in the vicinity of the heart. The electrodes are connected to the pacer by means of
15 leads. The internal parts of the pacers have to be well protected against the internal environment, especially the body fluids in the body for a long period of time, which places strict requirements on all entries into the interior of the can and especially on the connections of the leads to the housing. At the same time it should be possible to
20 disconnect the pacer from the implanted leads for replacement or servicing of the pacer. The connective parts of the pacer and the leads have largely been standardized so as to encompass a relatively deep female socket comprising a
25 number of contact surfaces whereas the leads are provided with a male part comprising one or several corresponding peripheral, generally circular contact surfaces.

30 At present the connective part of the pacer housing containing the female socket is made of a transparent material, normally of epoxy resin, which is molded onto the housing and onto contacts extending outwardly from the housing. The male part of the leads is normally locked by means of set-screws, although other fastening means have
35 been envisaged. The positioning and alignment of the different contact surfaces and of the fastening means or metallic threads for the set screws prior to the molding of the connective part is however very complicated and the

09830239-082001

It would thus be desirable if the molding procedure could be
5 dispensed with.

10

15

30

According to the invention the molding procedure can be avoided and the design of an interior socket can be

simplified to a high degree whilst still meeting the required high standards by designing a pacemaker housing in accordance with the appended main claim. Preferred embodiments are set forth in the dependent claims.

5

Short description of the appended drawings

Fig 1 shows a conventional pacemaker housing with a transparent, molded connective part;

10

Fig 2 shows a lead with a male connective part;

Figs 3 - 5 show a preferred embodiment of the connective part in accordance with the present invention;

15

Fig 6 illustrates an alternative embodiment of the invention.

Detailed description of preferred embodiments of the invention.

20

Fig 1 illustrates a conventional pacemaker housing 1 having a molded, transparent connective part 2. The connective part 2 includes a female socket 3. The inner end of the socket 3 is provided with a longitudinal bore 7 having a relatively small diameter. The bore 7 is provided with a contact surface 4 adjacent to which threads 5 for a set or lock screw are located in a bore 6 oriented orthogonally relative to the female socket. The housing is hermetically sealed also in relation to the molded part 2 and the contact between the interior electronics and the contact surface 4 is achieved by means of a feed-through. The feed-through comprises a ceramic plug, typically made of alumina, into which one or more leads have been soldered. This lead is bonded (e.g. ultrasonically welded) to the electronics and to the contact surface 4. The ceramic plug is soldered or brazed by means of gold into a sleeve made of titanium. This operation may be made at any time before the assembly of the

25

30

35

09830239-082001

pacemaker housing. The sleeve is welded into an opening in the housing in a sealing manner during the assembly of the pacemaker housing that normally consists of two halves. Before the connective part is molded onto the housing, these halves are welded together and sealed.

Fig 2 illustrates a lead 15 comprising a proximal connecting plug 10 and a distal, transvenous, intracardial electrode 16 as well as an attachment means 17 for suturing the proximal end of the lead in the body of the patient. The connecting plug 10 is designed to be received in the socket 3 and the end thereof is provided with a longitudinally projecting contact pin 11 as well as a cylindrical body 17 provided with sealing rings 12, 13, 14 intended to engage and seal against the corresponding inner cylindrical surface of the female socket 3. The shape of the pin 11 corresponds to the shape of the bore 7. When the plug 10 is inserted into the socket 3 the pin 11 engages the contact surface 4 and the set-screw in the bore 6 can be tightened against the pin 11 in order to securely lock the plug 10 in the socket 3. The complexities involved in holding the bores, contact surfaces and threads in position and keeping them open and free from the molding material during the molding process are evident.

For the sake of simplicity, the above prior art device has been illustrated as being unipolar. A bipolar embodiment naturally will be more complex to manufacture. The preferred embodiments of the invention described below will relate to bipolar embodiments.

Figs 3 - 5 show a preferred embodiment of the invention comprising a tubular member 20. For the sake of clarity, all reference signs have not been repeated throughout all drawings.

The member comprises a tube 21 with two open ends 22, 23. One end 22 is to be welded into an opening in the pacemaker housing. The tube is made of the same metal as the pacemaker

09030239-032001

housing, in this case titanium. The opposite end 23 of the tube is provided with a ceramic plug 26 fitting snugly in the tube and soldered with for instance gold against the inside of the tube. One contact ring 27 has been molded or
5 bonded into the ceramic plug.

The ceramic plug is provided with an interior bore corresponding to the shape of the proximal part of the male connector in the same way as the molded prior art female
10 connector described above and thus includes an interior sealing surface 53 for engagement with the sealing rings on the male connector.

The outer side of the outer end of the contact ring is free
15 from ceramic and extends out past the end of the tube 21, thus forming a contact surface for connection to the interior of the housing.

The inner bore of the ceramic plug is closed by a metal plug
20 28 having an inner bore at the inner end sized to correspond to the contact pin of the male connector and forming the innermost part of the inner bore of the ceramic plug. The inner bore of the metal plug also comprises an inner, circumferential groove 30. The outer end of the metal plug
25 extends out from the ceramic, past the end of the contact ring 27, thus forming a second contact surface. The metal plug may be molded into the ceramic or may be a separate part inserted and bonded into the inner bore of the ceramic plug.

30 The end part 31 of the inside of the contact ring is not covered with the ceramic material. In this way an inner circumferential groove is obtained in the inner bore of the ceramic plug. The bottom of the groove consists of the metal
35 in the contact ring.

Thus, when the ceramic plug 26 has been soldered or bonded into place, the second end 23 will be completely sealed by

09830230 082001

the plug 26 although allowing electrical connection to the interior of the tube via the contact ring 27 and the metal plug 28. It should be noted that several concentric contact rings in a staggered configuration separated by insulating ceramic material could be used. The number of the connections thus only would be limited by the constraints given by the dimensions.

The manufacturing steps involved in the above can be carried out in advance as desired so as to achieve a prefabricated tube.

The end of the prefabricated tube can be welded to the pacer housing and the housing parts can be welded together after the connection of interior leads from the interior electronics to the contact ring and the plug, should this be desired. The remaining parts, i. e. the means achieving the contact between the contact rings and the contact surfaces on the male connector part on the lead and the means locking or fixating the male connector part in the socket, can easily be inserted afterwards. This means for instance that these parts would not interfere with the standard helium-based procedures for testing the housing with connector for leaks or that these parts would not be affected by the leak testing procedure.

Fig 3 shows the main component parts of the tubular member, the tube 21 with the ceramic plug 26, a fixation part 40 and two circular spring contacts 50, 51. The spring contacts are similar to the spring contacts used in US-A-4,934,366.

The fixation part 40 is designed in a similar way as the lead locking device disclosed in US-A-4,262,982, herewith incorporated by reference,

The tube 21 preferably is of the same material as the pacer housing, which normally is made of titanium. The ceramic plug may for instance be made of alumina, Al_2O_3 , and the

09830239 082001

contact rings may for instance be made of stainless steel or of titanium.

Fig 4 shows the tubular connective member in an assembled state and Fig 5 shows the tubular connective member mounted in a pacer housing 60. The male connector plug 110 is shown inserted into the connective member.

The lead locking means 40 comprises a resilient ring 70 mounted in an interior, circumferential groove 71 in an inner sealing surface 54 in a hollow locking cylinder 41 fitting in the open end of the tube 21. The resilient ring is mounted so as to be located directly behind the hindmost sealing ring 116 on the plug 110. The resilient ring comprises an inner circumferential locking flange 72 biased inwardly into the central bore. When the plug 110 is inserted into the connective member, the sealing rings 112 - 116 thus will pass the flange and the hindmost sealing ring 116 will be held by the flange 72 against a movement outwardly from the connective member 40. Other lead locking means that could be used in this embodiment are for instance disclosed in US-A-4,934,366, which document thus is incorporated by reference.

Fig 5 shows how the tube has been mounted in a pacer housing 60 and welded to an opening 61 in the housing via flanges located on the outside of the tube ends. Fig 5 also shows a male connector plug 110 inserted in the tubular member. The plug has a contact pin 111, a contact surface 118 and four sealing rings 112, 113, 114, 116. The sealing rings 112 - 114, 116 are in engagement with the interior sealing surfaces 53, 54 and the spring contacts are in contact pin 111 respectively with the contact surface 118.

The connector means can be achieved in a simple way compared with the prior art molded connector means.

0930239-082001

20 The pacer then is finished by slipping the resilient spring contacts into the respective interior grooves in the ceramic plug and by inserting and bonding the lead locking means into place in the open end of the tube.

35 Since the tube after the welding operation in principle forms an integral part of the pacemaker housing, a high degree of tightness and integrity is obtained. The tube will ensure

a high strength and a high durability of the connective part, whilst the ceramic plug will ensure a high degree of tightness in view of the large contact area between ceramic plug and tube that can be used for soldering, i.e. sealing.

5

One important feature of the invention is the possibility of achieving a high capacitance between contact ring and tube. Ring and tube will be separated by the ceramic, which is chosen to be insulating and thus is a dielectricum.

10

The preferred embodiment naturally has a high capacitance since the contact ring has to extend a long way along the tube. This capacitance of course can be increased if a capacitor is connected in-between the outer tube and the contact ring.

15

In an alternative embodiment, illustrated in Fig 6, the mid-section of the tube is provided with two relatively small lateral openings 124, 125. The openings 124, 125 are sealed by means of a ceramic plug 126 fitting snugly in the tube and soldered with gold or otherwise bonded against the inside of the tube. Two contact rings 127, 128 have been molded into the ceramic plug.

20

The ceramic plug is provided with an interior bore corresponding to the shape of the proximal part of the male connector in the same way as the molded prior art female connector described above. The ceramic plug thus includes an interior sealing surface 153 for engagement with sealing rings on the male connector.

25

The central part 130, 131 of the inside of the contact rings is not covered with the ceramic material. In this way two inner circumferential grooves are obtained in the inner bore of the ceramic plug. The bottom of the grooves consists of the metal in the contact rings. Two openings 132, 133 are also provided in the outer surface of the ceramic plug that may be made to coincide with the lateral openings 124, 125

30

09030239.082001

in the tube wall. These openings give access to the contact rings 127, 128 when the ceramic plug has been mounted correctly in the tube 121. Leads for contacting the interior of the housing can be bonded to the parts of the contact rings 127, 128 accessible through the openings 124 125 and 132, 133.

Thus, when the ceramic plug 126 has been soldered or bonded into place, the openings 124, 125 will be completely sealed by the plug 126, although allowing electrical connection between the interior of the tube and the interior of the housing via the contact rings 127, 128.

The inner end 123 of the tube 121 is closed by means of a ceramic plug 170 soldered into the tube. The plug 170 may be made in one piece with the plug 126 or, as illustrated, in a separate piece.

The grooves 130, 131 contain spring contact rings 150, 151
20 of the same type as the ones described in the preferred
embodiment described above.

The locking means 140 are located in the same place and are identical to the locking means described in the above preferred embodiment. The locking means therefore are not described in more detail here.

It should be noted that the size of the openings 124, 125 being necessary to allow the bonding of the leads to the parts of the contact rings accessible through the openings 124, 125 and 131, 132 is small, seen in relation to the entire circumference and to the length of the tube. The openings thus do not affect the structural integrity of the tube. The contact rings 127, 128 moreover overlap the openings and are bonded thereto by means of the intermediate layer of ceramics, in this way strengthening the area in which said openings are located.

0000000000

Typical dimensions for a tube intended to house a standard IS-1 male connector are for instance an inner diameter of 5 mm, a wall thickness of 0.3 mm (i. e. the same as the thickness of typical pacer housing walls) and a diameter of the holes 124, 125 of about 2 mm. A minimum area of about 4 mm² is necessary for the equipment presently used for bonding leads to metallic surfaces. The length of the tube is of course adapted to the specific housing into which it is to be placed, but might typically be about 25 mm.

10

These dimensions of course can be varied as long as the tube remains structurally intact, i. e. as long as the tube has a strength and rigidity that is sufficient to prevent loads, including thermal stresses, on the housing and/or the connector to be transferred as tensile forces to the ceramic parts. Of course, low tensile forces not exceeding the tensile strength of the ceramic could be accepted. Since there are standards regarding the loads a pacer housing and connector should be able to withstand and regarding the overall tightness of the housing, variations of the dimensions only would involve standard stress calculations and dimensioning well within the scope of the man in the art. It should be noted that this also could take the degree of soldering between ceramic plug and tube into account, since this would determine the extent to which tube and ceramic would function as a composite without going outside the ordinary skill of the man skilled in the art.

15

20

25

30

The number of lateral openings of course only is limited by the length of the tube and by the above considerations regarding the structural integrity.

35

It should also be noted that the main design features of the above two embodiments could be combined in different ways. One or several of the connections of the above first embodiment thus could be combined with one or several connections according to the above second embodiment. For instance, should it be desired to provide four contact means

for a lead with four conductors, two of them could for instance be connected via an end plug designed in accordance with the first embodiment and the other two by means of lateral openings designed in accordance with the second
5 embodiment.

It should also be noted that the ceramic material in the connector partly or entirely could be replaced by another insulating material, for instance a suitable plastics
10 material.

09830239-082001